






IP price list
اردیبهشت 1402

1	DH-IPC-HFW5842EP-ZE		<p>8MP IR Vari-focal Bullet WizMind Network Camera</p> <ul style="list-style-type: none"> > 8MP 1/1.8" CMOS image sensor, low illuminance, high image definition (high definition image). > Outputs max. 8MP (3840× 2160) @30 fps. > Max. IR distance: 60 m. > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes > Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card. > 12V DC/PoE power supply. > ePoE, IP67, IK10 protection.> SMD 3.0 		<p>۲۷۲.۹۸۷.۰۰۰ ریال</p>
2	DH-IPC-HFW5541EP-ZE		<p>5MP IR Vari-focal Bullet WizMind Network Camera</p> <ul style="list-style-type: none"> > 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. > Outputs max. 5 MP (2592 × 1944)@20 fps. > Built-in IR LED, and the max. illumination distance is 60 m. > ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments. > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. > Three switchable intelligent resources: IVS, face detection, and people counting. > Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card. > 12 VDC/PoE power supply, easy for installation. > IP67 and IK10 protection; ePoE. > SMD 3.0. 		<p>۲۰۱.۹۲۰.۰۰۰ ریال</p>
3	DH-IPC-HFW5541TP-ASE		<ul style="list-style-type: none"> • 1/2.7" 5Megapixel progressive scan CMOS • ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments • 20 fps@2592 × 1944, 50/60 fps@1080P (1920 × 1080) • WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS • 2.8 mm fixed lens (3.6 mm, 6.0 mm, 8.0 mm, 12.0 mm optional) • 1/1 Alarm in/out, 1/1 audio in/out • Max. IR LEDs Length 80 m • Micro SD memory, IP67,IK10 		<p>۱۳۳.۷۱۶.۰۰۰ ریال</p>
4	DH-IPC-HFW5442EP-ZE		<ul style="list-style-type: none"> • 1/1.8" 4Megapixel progressive scan CMOS (AI-SATRLIGHT) • H.265 & H.264 triple-stream encoding • 25/30 fps@2688 × 1520, 50/60 fps@1080P(1920 × 1080) • WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS • 2.7 mm-12.0 mm motorized lens • 2/1 Alarm in/out, 1/1 audio in/out • Max. IR LEDs Length 50 m • Micro SD memory, IP67, IK10 		<p>۲۳۱.۰۵۵.۰۰۰ ریال</p>
5	DH-IPC-HFW3449EP-AS-LED		<ul style="list-style-type: none"> • 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition • Outputs max. 4MP (2688 × 1520) @ 30 fps • H.265 codec, high compression rate, low bit rate • Built-in Warm LED, max. LED distance: 30 m • ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments • Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes • Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) • Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection • Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic • 12V DC/PoE power support • IP67 protection · SMD Plus 		<p>۸۶.۶۷۰.۰۰۰ ریال</p>





























IP price list
اردیبهشت 1402

6	DH-IPC-HFW3441EP-SA		<ul style="list-style-type: none"> • 4MP, 1/3" CMOS image sensor, low illuminance, high image definition • Outputs max. 4MP (2688 × 1520)@30 fps • H.265 codec, high compression rate, low bit rate • Built-in IR LED, max. IR distance: 50 m • ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments • Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes • Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) • Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection • Supports max. 256 G Micro SD card, built-in Mic • 12V DC/POE power supply • IP67 protection · SMD Plus 		ریال ۷۲۰,۱۸۰,۰۰۰
7	DH-IPC-HFW3441EP-AS		<ul style="list-style-type: none"> • 4MP, 1/3" CMOS image sensor, low illuminance, high image definition • Outputs max. 4MP (2688 × 1520)@30 fps • H.265 codec, high compression rate, low bit rate • Built-in IR LED, max. IR distance: 50 m • ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments • Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes • Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) • Abnormality detection: Motion detection, video tampering, scene changing, audio abnormality detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection • Alarm: In, out; Audio: In, out; Supports max. 256 G Micro SD card, built-in Mic • 12V DC/POE power supply • IP67 protection · SMD Plus 		ریال ۷۵,۴۰۰,۰۰۰
8	DH-IPC-HFW2831TP-ZS		<ul style="list-style-type: none"> • 1/1.8" 8Megapixel progressive CMOS STARLIGHT • H.265 & H.264 dual-stream encoding • 25/30fps@8MP(3840×2160) • WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & • Micro SD card slot, up to 128GB: 3.7"11mm motorized lens • Max IR LEDs Length 60m· IP67, IK10(optional), PoE 		ریال ۵۱,۱۲۵,۰۰۰
9	DH-IPC-HFW2831SP-S		<p>8MP Lite IR Fixed-focal Bullet Network Camera</p> <ul style="list-style-type: none"> > 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition > Outputs max. 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps > H.265 codec, high compression rate, ultra-low bit rate > Built-in IR LED, max IR distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire · Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access,voltage detection > Supports max. 256 GB Micro SD card> 12V DC/PoE power supply> IP67 protection 		ریال ۱۱۱,۸۳۰,۰۰۰

IP price list
اردیبهشت 1402

10	DH-IPC-HFW2531TP-ZS	<ul style="list-style-type: none"> · 1/2.7" 5Megapixel progressive CMOS STARLIGHT · H.265 & H.264 dual-stream encoding · 15fps@5M(2592x1944)&25/30fps@3M(2304x1296) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB · IP67, PoE+ · 2.7~13.5mm motorized lens· Max IR LEDs Length 60m 		۱۲۲,۰۹۰,۰۰۰ ریال
11	DH-IPC-HFW2531SP-S	<ul style="list-style-type: none"> · 5MP Lite IR Fixed-focal Bullet Network Camera STARLIGHT · 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in IR LED, max IR distance: 30 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Intelligent detection: Intrusion, tripwire · Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection · Supports max. 256 GB Micro SD card · 12V DC/PoE power supply IP67 protection 		۷۰,۵۱۰,۰۰۰ ریال
12	DH-IPC-HFW2431TP-ZS	<ul style="list-style-type: none"> · 1/3" 4Megapixel progressive CMOS · H.265 & H.264 dual-stream encoding · 20fps@4M(2688x1520)&25/30fps@3M(2304x1296) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB · 2.7~13.5mm motorized lens· Max IR LEDs Length 60m · IP67, IK10(optional), PoE+ 		۹۹,۹۴۶,۵۰۰ ریال
13	DH-IPC-HFW2431SP-S	<ul style="list-style-type: none"> · 4MP, 1/3" CMOS image sensor, low illuminance, Starlight · Outputs 4MP (2560 × 1440)@25/30fps, Max. supports 4MP (2688 × 1520)@20 fps · H.265 codec, high compression ration, ultra-low bit rate · Built-in IR LED, max IR distance: 30 m · ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Intelligent detection: Intrusion, tripwire · IP67 protection · Abnormality detection: Motion detection, video tampering, no SD · Supports max. 256 GB Micro SD card · 12V DC/PoE power support 		۵۵,۱۲۰,۰۰۰ ریال
14	DH-IPC-HFW2231TP-ZS	<ul style="list-style-type: none"> · 1/2.8" 2Megapixel progressive STARVIS™ CMOS · H.265 & H.264 dual-stream encoding · 25/30fps@1080P(1920x1080) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB · 2.7~13.5mm motorized lens· Max IR LEDs Length 60m · IP67, IK10(optional), PoE 		۸۸,۲۱۰,۰۰۰ ریال

IP price list
اردیبهشت 1402

15	DH-IPC-HFW1831EP	<ul style="list-style-type: none"> • 1/1.8" 8Megapixel progressive scan CMOS • H.265&H.264 dual-stream encoding • 25/30fps@8MP(3840×2160) • WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 2.8mm fixed lens (4mm, 6mm optional) • Max. IR LEDs Length 50m ·IP67, PoE 		    	۱۱۵,۴۳۰,۰۰۰ ریال
16	DH-IPC-HFW1431SP	<ul style="list-style-type: none"> • 1/3" 4Megapixel progressive CMOS • H.265 & H.264 dual-stream encoding • 20fps@4M(2688×1520) &25/30fps@3M(2304×1296) • WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 2.8 mm fixed lens (3.6 mm optional) • Max IR LEDs Length 30m ·IP67, PoE 		    	۴۷,۵۰۵,۲۰۰ ریال
17	DH-IPC-HFW1431S1P	<ul style="list-style-type: none"> • 4MP, 1/3" CMOS image sensor, low illuminance, high image definition • Outputs 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP (2688 × 1520) @20 fps • H.265 codec, high compression rate, ultra-low bit rate • Built-in IR LED, max. IR distance: 30 m • ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments • Image flip, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes • Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection • 12V DC/PoE power support • IP67, protection 		   	۴۲,۶۷۴,۹۰۰ ریال
18	DH-IPC-HFW1230T1P-ZS	<ul style="list-style-type: none"> • 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition • Outputs max. 2MP (1920 × 1080p) @25/30 fps • H.265 codec, high compression rate, ultra-low bit rate • Built-in IR LED, max. IR distance: 50 m • ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments • Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes • Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access • Supports max. 256 GB Micro SD card • 12V DC/PoE power supply • IP67 protection 		    	۶۱,۵۳۶,۰۰۰ ریال
19	DH-IPC-HFW1230SP	<ul style="list-style-type: none"> • 1/2.7" 2Megapixel progressive CMOS • H.265& H.264 dual-stream encoding • 25/30fps@1080P(1920×1080) • DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 2.8 mm fixed lens (3.6mm optional) • Max IR LEDs Length 30m ·IP67, PoE 		   	۳۶,۹۱۰,۰۰۰ ریال





IP price list
اردیبهشت 1402

20	<p>IPC-A22EP</p>	<p>Human Detection 1080P 360° Coverage Built-in Siren Smart Tracking Privacy Mode Abnormal Sound Alarm Night Vision Two-way Talk Cloud</p>		۲۵,۱۲۰,۰۰۰ ریال
21	<p>DH-IPC-K100W</p>	<ul style="list-style-type: none"> • 1/3" 1.3Megapixel Aptina CMOS • H.264 & MJPEG dual-stream encoding • Max 15fps@1.3M (1280x960)/25/30fps@720P(1280x720) • DWDR, Day/Night, 2DNR, Auto iris, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 3.6mm fixed lens • White LEDs length 10m • PIR sensor range 6m • Micro SD memory . Wi-Fi 		۲۹,۳۰۰,۰۰۰ ریال
22	<p>DH-IPC-K22P</p>	<ul style="list-style-type: none"> . 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition . Outputs max. 2MP (1920 × 1080) @25/30 fps . H.265 codec, high compression rate, ultra-low bit rate . Max. IR distance: 10 m . Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes . H.264/H.265, flexible coding, applicable to various bandwidth and storage environments. . Alarm: 1 in, 1 out; 256 G SD card, built-in Mic and speaker . Supports 256 G Micro SD card . 12V DC power supply, easy for installation . Supports PIR . Supports Wi-Fi 		
23	<p>DH-IPC-HDBW5842EP-ZE</p>	<p>8MP IR Vari-focal Dome WizMind Network Camera</p> <ul style="list-style-type: none"> . 8 MP 1/1.8" CMOS image sensor, low luminance, and high definition image . Outputs max. 8MP (3840× 2160) @30 fps, Max. IR distance: 80 m . ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments . Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes . Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card . 24V AC/PoE/12V DC power supply . ePoE, IP67, IK10 protection, SMD 3.0 		۳۷,۸۳۰,۰۰۰ ریال
24	<p>DH-IPC-HDBW5831RP-ZE</p>	<p>8MP WDR IR Dome Network Camera</p> <ul style="list-style-type: none"> > 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS > H.265&H.264 dual-stream encoding > 15fps@4K(3840x2160),25/30fps@3M(2304x1296) > Day/Night(ICR), 3DNR, AWB, AGC, BLC > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS > 2.7mm ~12mm motorized lens > Max. IR LEDs Length 50m > Micro SD card memory, IP67,IK10, PoE 		
۱۸۵,۹۶۰,۰۰۰ ریال				






























IP price list
اردیبهشت 1402

25	DH-IPC-HDBW5541EP-ZE		<ul style="list-style-type: none"> · 1/2.7" 5Megapixel progressive scan CMOS · H.265&H.264 triple-stream encoding · 20fps@2592×1944 · WDR(120dB), Day/Night(ICR), 3D DNR, AWB, AGC, BLC · 2.7mm ~13.5mm motorized lens · 1/1 Alarm in/out, 1/1 audio in/out · Max. IR LEDs Length 40m · Micro SD memory, IP67, IK10 		۲۱۲,۲۰۰,۰۰۰ ریال
26	DH-IPC-HDBW5442EP-ZE		<ul style="list-style-type: none"> · 4MP IR Vari-focal Dome WizMind Network Camera · 1/1.8" 4Megapixel progressive scan CMOS · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · 25/30 fps@2688 × 1520, 50/60 fps@1080P (1920 × 1080) · WDR (140 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS · 2.7 mm~12.0 mm motorized lens . 1/1 Alarm in/out, 1/1 audio in/out · Max. IR LEDs Length 40 m . Micro SD memory, IP67, IK10 		۲۳۴,۹۷۲,۰۰۰ ریال
27	DH-IPC-HDW5541TMP-ASE		<ul style="list-style-type: none"> · 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. · Outputs max. 5 MP (2960 × 1668) @25/30fps. · Built-in IR LED, and the max. illumination distance is 50 m. · ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments. · Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. · With deep learning algorithm, it supports: video metadata, smart sound detection, IVS, face detection, smart object detection, and people counting, etc. · Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 512 GB Micro SD card, built-in MIC. · 12 VDC/PoE power supply; ePoE . IP67 protection . SMD 3.0. 		۱۲۶,۸۲۰,۰۰۰ ریال
28	DH-IPC-HDW5431RP-ZE		<ul style="list-style-type: none"> · 1/3" 4Megapixel progressive scan CMOS · H.265&H.264 triple-stream encoding · 25/30fps@4Mp(2688×1520) · Built-in Mic · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.7mm ~13.5mm motorized lens· Max. IR LEDs Length 50m · Micro SD card memory, IP67, PoE 		#N/A
29	DH-IPC-HDBW3441RP-ZS		<ul style="list-style-type: none"> · 4MP IR Vari-focal Dome WizSense Network Camera · 4MP, 1/3" CMOS image sensor, low illumination, high image definition · Outputs max. 4MP (2688 × 1520)@30 fps · H.265 codec, high compression rate, low bit rate · Built-in IR LED, max. IR distance: 40 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) · Abnormality detection: Motion detection, video tampering, scene changing, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection · Supports max. 256 G Micro SD card · 12V DC/POE power supply · IP67, IK10 protection, SMD Plus 		۱۲۱,۸۶۰,۰۰۰ ریال

IP price list
اردیبهشت 1402

30	DH-IPC-HDW3449TMP-AS-LED	<ul style="list-style-type: none"> · 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs max. 4MP (2688 × 1520) @ 30 fps · H.265 codec, high compression rate, low bit rate · Built-in Warm LED, max. LEDs distance: 30 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) · Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection · Supports max. 256 G Micro SD card, built-in Mic · 12V DC/PoE power support · IP67 protection · SMD Plus 	 <p>۸۶,۶۷۰,۰۰۰ ریال</p>
31	DH-IPC-HDBW3441EP-AS	<ul style="list-style-type: none"> · 4MP IR Fixed focal Dome WizSense Network Camera, STARLIGHT · 4MP, 1/3" CMOS image sensor, low illuminance, high image definition · Outputs max. 4MP (2688 × 1520)@30 fps · H.265 codec, high compression rate, low bit rate · Built-in IR LED, max. IR distance: 50 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) · Abnormality detection: Motion detection, video tampering, scene changing, audio abnormality detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection · Alarm: In, out; Audio: In, out; Supports max. 256 G Micro SD card · 12V DC/POE power supply · IP67, IK10 protection, SMD Plus 	 <p>۷۱,۸۰۰,۰۰۰ ریال</p>
32	DH-IPC-HDBW3441EP-S	<ul style="list-style-type: none"> · 4MP IR Fixed focal Dome WizSense Network Camera · 4MP, 1/3" CMOS image sensor, low illuminance, high image definition · Outputs max. 4MP (2688 × 1520)@30 fps · H.265 codec, high compression rate, low bit rate · Built-in IR LED, max. IR distance: 50 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) · Abnormality detection: Motion detection, video tampering, scene changing, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection · Supports max. 256 G Micro SD card · 12V DC/POE power supply · IP67, IK10 protection, SMD Plus 	 <p>۶۲,۷۸۰,۰۰۰ ریال</p>
33	DH-IPC-HDBW2831RP-ZS	<ul style="list-style-type: none"> · 1/1.8" 8Megapixel progressive CMOS · H.265 & H.264 dual-stream encoding · 25/30fps@8MP(3840×2160) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB · IP67, IK10, PoE · 3.7~11mm motorized lens· Max IR LEDs Length 30m 	 <p>۱۵۵,۰۶۲,۵۰۰ ریال</p>

IP price list
اردیبهشت 1402

34	DH-IPC-HDBW2531RP-ZS	<ul style="list-style-type: none"> 5MP WDR IR Dome Network Camera P6730m 1/2.7" 5Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 15fps@5M(2592x1944)&25/30fps@3M(2304x1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB 2.7~13.5mm motorized lens Max IR LEDs Length 30m, IP67, IK10, PoE 	     		115,430,000 ریال
35	DH-IPC-HDBW2431RP-ZS	<ul style="list-style-type: none"> 1/3" 4MP WDR IR Dome Network Camera H.265 & H.264 dual-stream encoding 20fps@4M(2688x1520)&25/30fps@3M(2304x1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB 2.7~13.5mm motorized lens Max IR LEDs Length 30m · IP67, IK10, PoE 	     		108,400,000 ریال
36	DH-IPC-HDBW2531EP-S	<ul style="list-style-type: none"> 5MP Lite IR Fixed-focal Dome Network Camera, STARLIGHT 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max IR distance: 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes Intelligent detection: Intrusion, tripwire Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection Supports max. 256 GB Micro SD card 12V DC/PoE power supply IP67, IK10 protection 	      		107,510,000 ریال
37	DH-IPC-HDW2439TP-AS-LED	<ul style="list-style-type: none"> 4MP Lite Full-color Fixed-focal Eyeball Network Camera 4MP, 1/3" CMOS image sensor, low illuminance, high image definition Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP (2688 × 1520) @ 20 fps H.265 codec, high compression rate, ultra-low bit rate Built-in warm lights, max. illumination distance: 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes Intelligent detection: Intrusion, tripwire Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection Supports max. 256 GB Micro SD card and built-in Mic 12V DC/PoE power supply, IP67 protection 	     		107,300,000 ریال

IP price list
اردیبهشت 1402

38	DH-IPC-HDBW2431EP-S	<ul style="list-style-type: none"> 4MP, 1/3" CMOS image sensor, low illumination, Starlight Outputs 4MP (2560 × 1440)@25/30 fps, max. supports 4MP H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max IR distance: 30 m ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes Intelligent detection: Intrusion, tripwire Abnormality detection: Motion detection, video tampering, no SD Supports max. 256 GB Micro SD card 12V DC/PoE power support · IP67, IK10 protection grade 			۵۵,۱۲۰,۰۰۰ ریال
39	DH-IPC-HDBW1431EP	<ul style="list-style-type: none"> 1/3" 4Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8 mm fixed lens (3.6 mm optional) Max IR LEDs Length 30m· IP67, IK10, PoE 			۲۲,۵۶۰,۰۰۰ ریال
40	DH-IPC-HDBW2231RP-ZS	<p>2MP WDR IR Dome Network Camera</p> <ul style="list-style-type: none"> 1/2.8" 2Megapixel progressive Starvis™ CMOS H.265 & H.264 dual-stream encoding 25/30fps@1080P(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB 2.7~13.5mm varifocal lens Max IR LEDs Length 30m IP67, IK10, PoE 			۷۹,۵۷۰,۰۰۰ ریال
41	DH-IPC-HDW1431T1P	<ul style="list-style-type: none"> 4MP, 1/3" CMOS image sensor, low illumination, high image definition Outputs 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP (2688 × 1520) @20 fps H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max. IR distance: 30 m ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments Image flip, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection 12V DC/PoE power support IP67, protection 			۴۵,۵۰۰,۰۰۰ ریال
42	DH-IPC-HDW2231TP-AS	<ul style="list-style-type: none"> 2MP, 1/2.8" CMOS image sensor, low illumination, high image definition Outputs max. 2MP (1920 × 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max. IR distance: 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes Intelligent detection: Intrusion, tripwire Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection Supports max. 256 GB Micro SD card, built-in Mic 12V DC/PoE power supply IP67 protection 			۵۱,۷۳۰,۰۰۰ ریال

IP price list
اردیبهشت 1402

43	DH-IPC-HDBW1230EP	<ul style="list-style-type: none"> . 1/2.7" 2Megapixel progressive CMOS . H.265 & H.264 dual-stream encoding . 25/30fps@1080P(1920x1080) . DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC . Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS . 2.8mm fixed lens (3.6mm optional) . Max IR LEDs length 30m . IP67, IK10, PoE 			۳۸,۴۶۰,۰۰۰ ریال
44	DH-IPC-HDW1230T1P	<ul style="list-style-type: none"> . 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition . Outputs max. 2MP (1920 × 1080p) @25/30 fps . H.265 codec, high compression rate, ultra-low bit rate . Built-in IR LED, max. IR distance: 30 m . ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments . Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes . Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access . 12V DC/PoE power support . IP67 protection 			۳۵,۳۵۶,۰۰۰ ریال
45	DH-IPC-HDW1239T1P-LED	<ul style="list-style-type: none"> . 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition . Outputs max. 2MP (1920 × 1080p) @25/30 fps . H.265 codec, high compression rate, ultra-low bit rate . Built-in LEDs, max LED distance: 15 m . ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments . Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes . Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access . 12V DC/PoE power support . IP67 protection 			۳۸,۴۶۰,۰۰۰ ریال
46	DH-IPC-HFW2439SP-SA-LED	<p>4MP Lite Full-color Fixed-focal Bullet Network Camera</p> <ul style="list-style-type: none"> . 4MP, 1/3" CMOS image sensor, low illuminance, high image definition . Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP (2688 × 1520) @ 20 fps . H.265 codec, high compression rate, ultra-low bit rate . Built-in warm lights, max. illumination distance: 30 m . ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments . Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes . Intelligent detection: Intrusion, tripwire . Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection . Supports max. 256 GB Micro SD card and built-in Mic . > 12V DC/PoE power supply . > IP67 protection 			۷,۴۸۰,۰۰۰ ریال

IP price list
اردیبهشت 1402

47	DH-IPC-HFW1239S1P-LED	<ul style="list-style-type: none"> · 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs max. 2MP (1920 × 1080) @25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in LEDs, max LED distance: 15 m · ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access · 12V DC/PoE power support · IP67 protection 		37,096,000 ریال
48	DH-IPC-HFW1230S1P	<ul style="list-style-type: none"> · 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs max. 2MP (1920 × 1080) @25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in IR LED, max. IR distance: 30 m · ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access · 12V DC/PoE power support · IP67 protection 		34,600,000 ریال
49	DH-SD5A245GB-HNR	<ul style="list-style-type: none"> > 1/2.8" 2Megapixel STARVIS™ CMOS. > 45x optical zoom. > Starlight technology. > Max. 25/30fps@1080P. > IR distance up to 150 m. > Auto-tracking 3.0. > Perimeter protection. > Face detection. > SMD 4.0. > Quick Pick. > IP67, IK10. 		33,010,000 ریال
50	DH-SD5A432XB-HNR	<ul style="list-style-type: none"> · 1/2.8" 4Megapixel STARVIS™ CMOS · Powerful 32x optical zoom · Max. 25/30fps@4M · IR distance up to 150 m · Deep-learning-based auto tracking and perimeter protection · SMD PLUS · PoE+ · IP67, IK10 · Face Detection 		30,225,000 ریال
51	DH-SD5A432GB-HNR	<ul style="list-style-type: none"> > 1/2.8" 4Megapixel STARVIS™ CMOS. > Powerful 32x optical zoom. > Max. 25/30 fps@4M. > IR distance up to 150 m. > Auto Tracking 3.0. > Face Detection. > SMD 4.0. > Quick Pick. > PoE+. > IP67, IK10. 		29,490,000 ریال





IP price list
اردیبهشت 1402

52	DH-SD5A232XB-HNR	<p>2MP 32x Starlight IR WizSense Network PTZ Camera</p> <ul style="list-style-type: none"> > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 32x optical zoom > Max. 50/60 fps@1080P > IR distance up to 150 m > Deep-learning-based auto tracking and perimeter protection > SMD PLUS > PoE+ > IP67, IK10 > Face Detection 		۴۸۹,۶۷۰,۰۰۰ ریال
53	DH-SD59230U-HNI	<p>2MP 32x Starlight IR WizSense Network PTZ Camera</p> <ul style="list-style-type: none"> > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 32x optical zoom > Max. 50/60 fps@1080P > IR distance up to 150 m > Deep-learning-based auto tracking and perimeter protection > SMD PLUS > PoE+ > IP67, IK10 > Face Detection 		۵۱۰,۴۰۰,۰۰۰ ریال
54	DH-SD49225XA-HNR	<p>2MP 25x Starlight IR WizSense Network PTZ Camera</p> <ul style="list-style-type: none"> 1/2.8" 2Megapixel CMOS Powerful 25x optical zoom Starlight technology Max. 50/60fps@1080P Perimeter protection . Support PoE+ IR distance up to 100m . SMD PLUS . IP66 		۲۹۱,۳۱۹,۰۰۰ ریال
55	DH-SD29204UE-GN	<ul style="list-style-type: none"> 1/2.8" STARVIS™ CMOS . STARLIGHT Powerful 4x optical zoom Support Triple-streams encoding WDR, Day/Night(ICR), Ultra DNR Max. 25/30fps@1080P . IVS Support PoE . IR distance up to 30m 		۱۴۴,۹۲۰,۰۰۰ ریال
56	DH-NVR1B04 	<p>4 Channel Smart 1U H.265 Network Video Recorder decoding</p> <ul style="list-style-type: none"> Max 4 channel IP camera inputs Max 80Mbps incoming bandwidth Up to 8MP resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output 		۲۸,۲۴۰,۰۰۰ ریال
57	DH-NVR1B04-4P 	<p>4 Channel Smart 1U H.265 Network Video Recorder decoding</p> <ul style="list-style-type: none"> Max 4 channel IP camera inputs Max 80Mbps incoming bandwidth Up to 8MP resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support IPC UPnP, 4PoE ports 1 SATA III Port, up to 6TB capacity for each HDD 		۴۵,۷۲۰,۰۰۰ ریال






IP price list
اردیبهشت 1402

58	DH-NVR104-P <i>EZ-IP</i>	<ul style="list-style-type: none"> . 4CH Smart Box 4PoE Network Video Recorder . Up to 4 channel IP camera input . H.264/MJPEG dual codec decoding . Max 56Mbps incoming bandwidth . HDMI/VGA simultaneous video output . All channel synchronous realtime playback, GRID interface . Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0 . Support IPC UPnP, 4PoE ports . Support P2P (QR code Scan) 		۴۱۰۳۰,۰۰۰ ریال
59	DH-NVR108-P <i>EZ-IP</i>	<ul style="list-style-type: none"> . 8CH Smart Box 4PoE Network Video Recorder . Up to 8 channel IP camera input . H.264/MJPEG dual codec decoding . Max 56Mbps incoming bandwidth . HDMI/VGA simultaneous video output . All channel synchronous realtime playback, GRID interface . Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0 . Support IPC UPnP, 4PoE ports . Support P2P (QR code Scan) 		۴۷۸۲۰,۰۰۰ ریال
60	DH-NVR608-64-4KS2	<ul style="list-style-type: none"> . Intel Quad-core Processor . 64 channel IPC input-32 Channel Live Preview: (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16) . H.265/H.264/MJPEG codec decoding . Max 384Mbps incoming bandwidth . 2HDMI/VGA simultaneous video output . Up to 12Mp resolution preview & playback . RS232 , RS485-16 Alarm In . Support 8 SATA HDDs up to 64TB,1 eSATA Port . Support Raid 0/1/5/6/10 . Support Smart Tracking and Intelligent Video . 4 USB(2 USB3.0, 2 USB2.0)-2*1000 Mbps Network Card 		۹۰۸۰۸۰,۰۰۰ ریال
61	DH-NVR608H-32-XI	<ul style="list-style-type: none"> . 32 Channels 2U 8HDDs WizMind Network Video Recorder . > 32-channel 1080p self-adaptive decoding capability. . > Max. 1024/1024/800Mbps incoming/recording/outgoing bandwidth. . > Supports N+M cluster. . > Support Raid0/1/5/6/10. . > Drawer-like chassis design allows for HDD hot swapping. . > AI by recorder: 4-channel face detection and recognition; 8-channel metadata; 24-channel perimeter protection; 32-channel SMD Plus. . > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, and people counting. 		۱۰۶۱۰۰۰,۰۰۰ ریال
62	DH-NVR608-32-4KS2	<ul style="list-style-type: none"> . Intel Dual-core Processor-32 channel IPC input . 32 Channel Live Preview.: 16 Alarm In , 8 Relay Output . (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) . H.265/H.264/MJPEG codec decoding . Max 384Mbps incoming bandwidth . Up to 12Mp resolution preview&playback . 2HDMI/VGA simultaneous video output . Support 8 SATA HDDs up to 64TB,1 eSATA Port . Support Raid 0/1/5/6/10-4 USB(2 USB3.0, 2 USB2.0) . 2*1000 Mbps Network Card-RS232 , RS485 		۵۰۲۰۹۵۷,۰۰۰ ریال











IP price list
اردیبهشت 1402

63	DH-NVR5864-EI	<p>64 Channels 2U 8HDD WizSense Network Video Recorder</p> <ul style="list-style-type: none"> > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. > 32-channel 1080p self-adaptive decoding capability. > Support Raid0/1/5/6/10. > Max. 384 Mbps incoming/recording/outgoing bandwidth. > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. > Security baseline 2.3. 	 <p>۳۹,۷۰۰,۰۰۰ ریال</p>
64	DH-NVR5832-EI	<p>32 Channels 2U 8HDD WizSense Network Video Recorder</p> <ul style="list-style-type: none"> > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. > 32-channel 1080p self-adaptive decoding capability. > Max. 384 Mbps incoming/recording/outgoing bandwidth. > Support Raid0/1/5/6/10. > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. > Security baseline 2.3. 	 <p>۵۶,۷۰۰,۰۰۰ ریال</p>
65	DH-NVR5832-4KS2	<ul style="list-style-type: none"> . 32 channel IPC input-32 Channel Live Preview . H.265/H.264/MJPEG/MPEG4 codec decoding . Max 320Mbps incoming bandwidth . P2P Support-Raid 0/1/5/6/10 . Up to 12MP resolution preview&playback . Max 16ch@1080P 4ch@4K H.265 H.264 Playback . 2HDMI/VGA simultaneous video output . Support 8 SATA HDDs up to 64TB, 4 USB(2 USB3.0, 2 USB2.0) . 2*1000 Mbps Network Card-RS232-16 Alarm In , 6 Relay Output 	 <p>۴۴۷,۸۷۶,۰۰۰ ریال</p>
66	DH-NVR5432-16P-4KS2E	<ul style="list-style-type: none"> . 32Channel 1.5U 16PoE 4K&H.265 Pro Network Video Recorder . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG . Max 320Mbps Incoming Bandwidth . Up to 12MP Resolution for Preview and Playback . 2HDMI/VGA simultaneous video output . 3D intelligent positioning with Dahua PTZ camera . 4 SATA III Ports, Up to 8 TB capacity for each HDD 	 <p>۴۶۱,۲۳۰,۰۰۰ ریال</p>





IP price list
اردیبهشت 1402

67	DH-NVR5432-EI	<p>32 Channels 1.5U 4HDD WizSense Network Video Recorder</p> <ul style="list-style-type: none"> > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. > 32-channel 1080p self-adaptive decoding capability. > Max. 384 Mbps incoming/recording/outgoing bandwidth. > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. > Security baseline 2.3. 		ریال ۳۹۳,۱۹۰,۰۰۰
68	DH-NVR5432-4KS2	<p>32 Channel 1.5U 16PoE 4K&H.265 Pro Network Video Recorder</p> <ul style="list-style-type: none"> Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps Incoming Bandwidth Up to 12MP Resolution for Preview and Playback 2HDMI/2VGA simultaneous video output 1-8 PoE Ports Support 800m ePoE & EoC 		ریال ۳۱۳,۳۷۵,۰۰۰
69	DH-NVR5232-EI	<p>32 Channels 1U 2HDD WizSense Network Video Recorder</p> <ul style="list-style-type: none"> > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. > 32-channel 1080p self-adaptive decoding capability. > Max. 384 Mbps incoming/recording/outgoing bandwidth. > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. > Security baseline 2.3. 		ریال ۲۷۵,۵۹۰,۰۰۰
70	DH-NVR5232-4KS2	<p>32 channel IP camera input. 32 channel Live Preview</p> <ul style="list-style-type: none"> Up to 12Mp resolution preview&playback Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps incoming bandwidth-Record Rate 320 Mbps Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding HDMI/VGA simultaneous video output-16 channel playback Support 2 SATA HDDs up to 20TB, 2 USB(1 USB3.0) 1000 Mbps Network Card -RS232, RS485 4 Alarm Input, 2 Relay Output-Support P2 		ریال ۲۴۴,۶۲۲,۴۰۰
71	DH-NVR5216-16P-I	<p>16Channel 1U 16PoE AI Network Video Recorder</p> <ul style="list-style-type: none"> 16 Channel IP video access Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Up to 16 Channel perimeter protection Up to 4 Channel video stream face recognition Up to 22 face pictures /sec processing Up to 20 face databases with 100,000 face images in total 1-8 PoE Ports support ePoE & EoC 		ریال ۶۷۰,۰۴۰,۰۰۰

IP price list
اردیبهشت 1402

72	DH-NVR5216-16P-4KS2E	<ul style="list-style-type: none"> .32 Channel 1U 2HDDs 16PoE 4K & H.265 Pro Network Video Recorder . 32-channel IP video access . Smart H.265+/Smart H.264+/H.264/MJPEG; H.265 auto switch . Max 320 Mbps incoming bandwidth . Up to 24MP resolution for live view and playback . 1-channel fisheye dewarping (AI by NVR) . AI by Camera: Perimeter protection; face detection and recognition; SMD Plus; video metadata; . ANPR; people counting; stereo analysis; crowd distribution; heat map . Support IPC UPnP, 16 PoE ports 			۲۸۷,۷۴۱,۵۰۰ ریال
73	DH-NVR5216-EI	<ul style="list-style-type: none"> 16 Channels 1U 2HDD WizSense Network Video Recorder > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. > 32-channel 1080p self-adaptive decoding capability. > Max. 384 Mbps incoming/recording/outgoing bandwidth. > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. > Security baseline 2.3 			۲۴۵,۰۷۰,۰۰۰ ریال
74	DH-NVR5216-4KS2	<ul style="list-style-type: none"> . 16Channel 1U 4K&H.265 Pro Network Video Recorder (V2.00) . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG . Max 320Mbps Incoming Bandwidth . Up to 12MP Resolution for Preview and Playback . HDMI/VGA simultaneous video output . 2 SATA III Ports, Up to 10 TB capacity for each HDD 			۲۰۷,۴۶۰,۰۰۰ ریال
75	DH-NVR4432-4KS2	<ul style="list-style-type: none"> . 32 channel IP camera input. 1.5U . 16 channel Live Preview-H.265/H.264 codec decoding . Max 200Mbps incoming bandwidth . Up to 8MP Resolution for Preview and Playback . HDMI/VGA simultaneous video output . Support 4 SATA HDD up to 6TB . 2 USB Ports (1 USB2.0, 1 USB3.0) . 16 Alarm Input, 4 Relay Output-RS232 , RS485 . 2*10/100/1000Mbps Mbps Network Card-P2P support 			۱۹۹,۸۱۰,۰۰۰ ریال
76	DH-NVR4232-4KS2/L	<ul style="list-style-type: none"> . New 4.0 user interface, Security baseline 2.1 . H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch . Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding . Supports mainstream cameras of ONVIF and RTSP protocols . P2P remote surveillance, video play on mobile device . VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K . AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD . Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 			۴۰۶,۰۰۰ ریال






IP price list
اردیبهشت 1402

77	DH-NVR4232-4KS2	<ul style="list-style-type: none"> 32-channel IP video access Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch Max 200 Mbps incoming bandwidth Up to 8MP resolution for preview and playback 8-channel decoding@1080p (30 fps) AI by Camera: Perimeter protection; SMD Plus; people counting; heat map 	 ۱۴۳,۳۹۰,۰۰۰ ریال
78	DH-NVR4216-16P-4KS2/L	<p>16 Channel 1U 2HDDs 16PoE Network Video Recorder- New 4.0 user interface, Security baseline 2.1</p> <ul style="list-style-type: none"> H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	 ۱۹۳,۱۷۷,۰۰۰ ریال
79	DH-NVR4216-4KS2/L	<p>16 Channel 1U 2HDDs Network Video Recorder</p> <ul style="list-style-type: none"> New 4.0 user interface, Security baseline 2.1 H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	 ۱۱۳,۰۲۲,۰۰۰ ریال
80	DH-NVR4116HS-4KS2/L	<ul style="list-style-type: none"> New 4.0 user interface, Security baseline 2.1 H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	 ۹۴,۰۹۰,۰۰۰ ریال

IP price list
اردیبهشت 1402

81	DH-NVR4108HS-8P-4KS2/L	<ul style="list-style-type: none"> • New 4.0 user interface, Security baseline 2.1 • H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch • Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding • Supports mainstream cameras of ONVIF and RTSP protocols • P2P remote surveillance, video play on mobile device • VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K • AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD • Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	 ۵۱.۷۶۷,۰۰۰ ریال
82	DH-NVR4108HS-4KS2	<ul style="list-style-type: none"> • 8 Channel Compact 1U 4K&H.265 Lite Network Video Recorder • Smart H.265+/H.265/Smart H.264+/H.264 • Max 80Mbps Incoming Bandwidth • Up to 8MP Resolution for Preview and Playback • Up to 2ch@4K/8ch@1080P decoding • HDMI/VGA simultaneous video output 	 ۵.۵۲۰,۰۰۰ ریال
83	DH-NVR4108HS-4KS2/L	<ul style="list-style-type: none"> • New 4.0 user interface, Security baseline 2.1 • H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch • Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding • Supports mainstream cameras of ONVIF and RTSP protocols • P2P remote surveillance, video play on mobile device • VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K • AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD • Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	 ۹.۹۶۰,۰۰۰ ریال
84	DH-NVR4104HS-P-4KS2/L	<ul style="list-style-type: none"> • 4 Channel Compact 1U 1HDD 4PoE Network Video Recorder • New 4.0 user interface, Security baseline 2.1 • H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch • Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding • Supports mainstream cameras of ONVIF and RTSP protocols • P2P remote surveillance, video play on mobile device • VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K • AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD • Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	 ۹.۸۶۸.۸۰۰ ریال

IP price list
اردیبهشت 1402

85	DH-NVR4104HS-4KS2/L	<ul style="list-style-type: none"> . 4 Channel Compact 1U 1HDD Network Video Recorder .. New 4.0 user interface, Security baseline 2.1 . H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch . Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding . Supports mainstream cameras of ONVIF and RTSP protocols . P2P remote surveillance, video play on mobile device . VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K . AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SIMD . Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 		۱,۰۴۰,۰۰۰ ریال
86	DH-NVR2108HS-8P-4KS2	<ul style="list-style-type: none"> . 8 Channel Compact 1U 8PoE Lite 4K . H.265/H.264 codec decoding . HDMI/VGA simultaneous video output . Max 80Mbps incoming bandwidth . Up to 8Mp resolution preview&playback . Up to 1ch@8MP/4ch@1080P decoding . Support 1 SATA HDD up to 6TB, 2 USB2.0 . 100 Mbps Network Card-8Port PoE. P2P support 		۱,۰۹۰,۰۰۰ ریال
87	DH-NVR2104HS-P-4KS2	<ul style="list-style-type: none"> . 4 Channel Compact 1U 4PoE Lite 4K. H.265/H.264 codec decoding . Max 80Mbps incoming bandwidth-Up to 8Mp resolution . preview&playback-Up to 1ch@8MP/4ch@1080P decoding . HDMI/VGA simultaneous video output . Support 1 SATA HDD up to 6TB, 2 USB2.0 . 100 Mbps Network Card-4PoE Port. P2P support 		۷۶,۹۴۰,۰۰۰ ریال
88	DH-NVR2108HS-4KS2	<ul style="list-style-type: none"> . 8 channel IP camera input 1U Lite 4K . H.265/H.264 codec decoding . 100 Mbps Network Card. P2P support . Max 80Mbps incoming bandwidth . HDMI/VGA simultaneous video output . Up to 8Mp resolution preview&playback . Up to 1ch@8MP/4ch@1080P decoding . Support 1 SATA HDD up to 6TB, 2 USB2.0 		۵۶,۴۲۰,۰۰۰ ریال
89	DH-NVR2104HS-4KS2	<ul style="list-style-type: none"> . 4 channel IP camera input 1U Lite 4K . H.265/H.264 codec decoding . 100 Mbps Network Card. P2P support . Max 80Mbps incoming bandwidth . HDMI/VGA simultaneous video output . Up to 8Mp resolution preview&playback . Up to 1ch@8MP/4ch@1080P decoding . Support 1 SATA HDD up to 6TB, 2 USB2.0 		۴۸,۷۳۰,۰۰۰ ریال

IP price list
اردیبهشت 1402

90	DH-NVR1108HS-8P-S3/H	<ul style="list-style-type: none"> • New 4.0 user interface • P2P remote surveillance, video play on mobile device • 8-ch@1080P(30FPS), self-adaptive decoding capability • Support for mainstream cameras of ONVIF and RTSP protocol • Smart H.265+/Smart H.264+/H.265/H.264 • VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P • Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches • DHCP(Dynamic Host Configuration Protocol), HTTP(Hypertext Transfer Protocol), NTP(Network Time Protocol) and DDNS(Dynamic Domain Name System) 		۷۴,۶۳۰,۰۰۰ ریال
91	DH-NVR1104HS-P-S3/H	<ul style="list-style-type: none"> • New 4.0 user interface • P2P remote surveillance, video play on mobile device • 4-ch@1080P(30FPS), self-adaptive decoding capability • Support for mainstream cameras of ONVIF and RTSP protocol • Smart H.265+/Smart H.264+/H.265/H.264 • VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P • Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches • DHCP(Dynamic Host Configuration Protocol), HTTP(Hypertext Transfer Protocol), NTP(Network Time Protocol) and DDNS(Dynamic Domain Name System) 		۵۲,۵۴۰,۰۰۰ ریال
92	DH-PFS3226-24ET-240	<ul style="list-style-type: none"> > Intelligent PoE > PD Alive(PoE Watchdog) > Long Distance PoE Transmission > Smooth Transmission > Wide Working Temperature: -10 to 55°C (14°F to 131°F) > Port Isolation 		۱۹۷,۳۶۰,۰۰۰ ریال
93	DH-PFS3218-16ET-135	<ul style="list-style-type: none"> > Intelligent PoE > PD Alive(PoE Watchdog) \ > Long Distance PoE Transmission > Smooth Transmission > Wide Working Temperature: -10 to 55°C (14°F to 131°F) > Port Isolation 		۱۵۰,۹۸۸,۰۰۰ ریال
94	DH-PFS3010-8ET-96	<ul style="list-style-type: none"> • 8-Port PoE Switch (Unmanaged) . Layer two commercial switch • Supports PoE power management • Supports wall-mount installation · Supports anti-theft lock hole • MAC auto learning and aging, MAC address capacity is 16K • Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards • RJ45 port supports 10/100 Mbps self-adaptation • Supports 250 meters long distance PoE transmission • Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply 		۶۴,۹۰۰,۰۰۰ ریال
95	DH-PFS3106-4ET-60	<ul style="list-style-type: none"> • 4-Port PoE Switch (Unmanaged) • Layer two Hardened PoE switch • Supports PoE power management • MAC auto learning and aging, MAC address capacity is 8K • Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply • Supports IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards • Wide working temperature design: -30°C~ 65°C · Supports dual power backup 		۵۷,۷۰۰,۰۰۰ ریال

IP price list

اردیبهشت 1402

96	DH-PFS3102-1T	<ul style="list-style-type: none"> 2-layer industrial level Ethernet media converter Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards 100M/1000M self-adaptive SFP fiber port Industrial wide temperature design 		۲۶,۸۹۰,۰۰۰ ریال
97	DH-LR2218-16ET-240	<ul style="list-style-type: none"> 16-Port ePoE Switch Supports long distance PoE transmission up to 800m with ePoE technology of Dahua Layer-two web managed ePoE switch Port 1-8 support three self-adaptive transmission modes which are IEEE, E100 and E10 Port 1-8 support both twisted-pair transmission and coaxial cable transmission Support web management: port management, 802.1Q VLAN, STP/RSTP, LACP, 802.1X, QoS Support PoE management, Green PoE, Legacy Support Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and 		۲۰,۵۲۱۰,۰۰۰ ریال
98	DH-LR2110-8ET-120	<ul style="list-style-type: none"> 8-Port ePoE Switch Supports long distance PoE transmission up to 800m with ePoE technology of Dahua Layer-two ePoE switch MAC auto study and aging, MAC address list capacity is 8K Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards Supports IEEE802.3af, IEEE802.3at, Hi-PoE standard Industrial wide temperature design Port indicator light is to display the status of current transmission mode for the port, which includes IEEE, E100 and E10 		۱۲۱,۸۳۰,۰۰۰ ریال
99	DH-PFL2106-4ET-96	<ul style="list-style-type: none"> 4-Port ePoE Switch Supports long distance PoE transmission up to 800m with ePoE technology of Dahua Two-layer industrial PoE switch MAC auto study and aging, MAC address list capacity is 8K Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards Supports IEEE802.3af, IEEE802.3at, Hi-PoE standard Industrial wide temperature design 		۸۰,۷۷۰,۰۰۰ ریال
100	DH-NKB1000-E	<p>Keyboard to Control</p> <ul style="list-style-type: none"> Dahua High Speed Dome · Dahua Standalone DVR Network Video Server Connection RS485, RS422 (reserved), USB, RS232 & Network Functions Three Dimensional Joystick Control of PTZ Functions Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions On-Screen Menu & User Operation Procedure Tips Connect to SmartPSS or DSS platform via USB 		۱۶۹,۹۰۰,۰۰۰ ریال
101	DH-PFM900-E	<p>Integrated Mount Tester</p> <ul style="list-style-type: none"> > 4.0" TFT screen, 800 × 480 resolution > H.264/H.265 decoding display for IPC > HDCVI/AHD/TVI/CVBS video display control > Support SD and HD direct switch > 12V/2A DC power supply for the camera > Support RS-485 control, and audio test > Length and attenuation tests of the network cable > Functions of digital multimeter 		۴۸۳,۰۰۰,۰۰۰ ریال