




























Network Camera - NVR

SKU(M)	Items	Description	User Price
spark			
1	TC-C32QN Spec: I3/E/Y/2.8mm/V5.0	 KEY FEATURES -Metal+Plastic Housing -Up to 1920x1080@25fps -S+265/H.265/H.264 -Min. illumination Color: 0.02Lux@F2.0 -Smart IR, IR Range: 30m, -Built-in Mic -Operating Conditions -30°-60°, 0-95% RH -POE, IP67	IRR 20,000,000
3	TC-C32XN Spec: I3/E/Y/2.8mm/V5.0	 -Up to 1920x1080@30fps -S+265/H.265/H.264 -Min. illumination Color: 0.02Lux@F2.0 -Smart IR, IR Range: 30m -Operating Conditions -30°-60°, 0-95% RH-POE	IRR 20,000,000
2	TC-C34QN Spec: I3/E/Y/4mm/V5.0	 KEY FEATURES -Metal+Plastic Housing -Up to 1920x1080@25fps -S+265/H.265/H.264 -Min. illumination Color: 0.02Lux@F2.0 -Smart IR, IR Range: 30m, -Built-in Mic -Operating Conditions -30°-60°, 0-95% RH -POE, IP67	IRR 29,900,000
4	TC-C34XN Spec: I3/E/Y/2.8mm/V5.0	 -Up to 1920x1080@30fps -S+265/H.265/H.264 -Min. illumination Color: 0.02Lux@F2.0 -Smart IR, IR Range: 30m -Operating Conditions -30°-60°, 0-95% RH-POE	IRR 28,600,000
5	TC-R3105 SPEC: I/B/L/S/EU	 5-ch, 50Mbps/40Mbps, recording resolution up to 6MP, decoding ability 1*6MP, 3*1080p, 4*720p, video output: 1 HDMI & 1 VGA simultaneous output, USB interface: 2xUSB 2.0	IRR 34,270,000
6	TC-R3105 SPEC: I/B/P/L/S	 5CH 1HDD 1U NVR, 5 IP camera input + 2 CH expansion = 7CH S+265/H.265/H.264 video formats Max 50/40 Mbps incoming/Outgoing bandwidth, Up to 6M Resolution Recording Synchronous Decode: 1x6MP, 3x1080P, VCA detection alarm is supported HDMI and VGA simultaneous output, HDMI Video output at up to 1080P (1920 x 1080) 1 SATA interface, up to 10TB for 1 HDD 1CH Audio output, 2 USB Ports 1*10/100 Mbps Network Card, P2P support	IRR 52,910,000
7	TC-R3110 SPEC: I/B/L/S/EU	 -S+265/H.265/H.264 video formats -Connectable to the third-party network cameras -Support live view, storage, and playback of the connected camera at up to 6MP resolution -1xHDMI and 1xVGA simultaneous outputs -HDMI Video output at up to 4K resolution, HD Storage -1 SATA interface, up to 8TB for 1 HDD -S+265 compression effectively reduces the storage space and costs by up to 75% -1xRJ45 self-adaptive 10/100 Mbps network interface/Various Applications	IRR 39,100,000
8	TC-R3110 SPEC: I/B/P8/L/S	 HD Input -Plug and play -S+265/H.265/H.264 video formats -Connectable to the third-party network cameras -Up to 10-channel input -8 PoE ports- Supports live view, storage, and playback of the connected camera at up to 8MP resolution/HD Output -1xHDMI and 1xVGA simultaneous output -HDMI Video output at up to 4K (3840 x 2160) resolution HD Storage- 1 SATA interface, up to 10TB for 1 HDD -Support 250m long-distance transmission	IRR 63,745,000
9	TC-C32KN I3/Y/WIFI/2.8MM	 -Metal+Plastic Housing -Up to 1920x1080@30fps -S+265/H.265/H.264 -Min. illumination Color: 0.02Lux@F2.0 -Smart IR, IR Range: 30m -Operating Conditions -35°C-65°C, 0-95% RH -Built-in Mic, SD Card Slot, Reset Button -Support Wi-Fi -IP67, IK10	IRR 46,095,000
10	TC-C32WN I5/Y/WIFI/4MM/V4.0	 -Metal+Plastic Housing -Up to 1920x1080@30fps -S+265/H.265/H.264 -Min. illumination Color: 0.02Lux@F2.0 -Smart IR, IR Range: 30m -Operating Conditions -35°C-65°C, 0-95% RH -Built-in Mic, SD Card Slot, Reset Button -Support Wi-Fi -IP67	IRR 46,095,000

11	TC-H334S ISW/C/WIFI/4MM/4.1		<ul style="list-style-type: none"> -Metal+Plastic Housing -Up to 2304x1296@25fps -S+265/H.265/H.264 -Min. illumination Color: 0.02Lux@F1.6 -Smart IR, IR Range: 50m -White Light : 20-30m -Operating Conditions -30°C-60°C, 0-95% RH -Built-in Mic, SD Card Slot, Reset Button -Support Wi-Fi 	IRR 65,550,000
super lite series				
12	TC-C32GN Spec:15/E/Y/C/2.8mm/V4.2		<ul style="list-style-type: none"> 1920x1080@30fps, Metal+Plastic 1/2.8", 0.02Lux, WDR 120dB, 50m IR FOV: 99.7°, S+265/H.265/H.264, IP67 Mic-in, No Power Cable, No Reset Bottom, 512GB SD-Card 	IRR 25,300,000
16	TC-C32HN Spec:13/E/Y/C/2.8mm/V4.2		<ul style="list-style-type: none"> Metal+Plastic Housing -Up to 1920x1080@30fps -S+265/H.265/H.264 -Min. illumination Color: 0.02Lux@F2.0 Smart IR, IR Range: 30m-Built-In Mic -Support tripwire and perimeter -Operating Conditions -30°C-60°C, 0-95% RH -POE, IP66 	IRR 25,300,000
13	TC-C32GN Spec:15/E/Y/C/2.8mm/V4.1		<ul style="list-style-type: none"> 1920x1080@30fps, Metal+Plastic 1/2.8", 0.02Lux, WDR 120dB, 50m IR FOV: 99.7°, S+265/H.265/H.264, IP67 Mic-in, No Power Cable, No Reset Bottom, 512GB SD-Card 	IRR 28,762,800
15	TC-C32HN Spec: 13/E/Y/C/2.8mm/V4.1		1/2.8" CMOS, F2.0, Fixed Iris, Digital WDR, 30m IR, 0.02Lux, 1920x1080@30fps, Built-in Mic, IP67, PoE, Metal+Plastic housing, No Power Cable	IRR 28,762,800
14	TC-C32GN 15/E/Y/C/SD/2.8mm/V4.1		<ul style="list-style-type: none"> 2MP Fixed IR Bullet Camera 1920x1080@30fps, Metal+Plastic, 1/2.8", 0.02Lux, Digital WDR, 50m IR FOV: 99.7°, S+265/H.265/H.264, IP67 Mic-in, No Power Cable, No Reset Bottom, 	IRR 31,240,000
17	TC-C34GN Spec:15/E/Y/C/2.8mm/V4.2		<ul style="list-style-type: none"> 2560x1440@25fps, Metal+Plastic, 1/2.7", 0.02Lux, Digital WDR, 50m IR FOV: 103.4°, S+265/H.265/H.264, IP67 Mic-in, No Power Cable, No Reset Bottom, No SD-Card 	IRR 36,800,000
18	TC-C34HN Spec:13/E/Y/C/2.8mm/V4.2		4MP Fixed IR Turret Camera 2560x1440@25fps, Metal+Plastic 1/2.7", 0.02Lux, Digital WDR, 30m IR FOV: 99.7°, S+265/H.265/H.264, IP66 Mic-in, No Power Cable, No Reset Bottom, No SD-Card	IRR 35,200,000
20	TC-C34GS Spec: 15/E/Y/C/2.8MM/V4.0		<ul style="list-style-type: none"> 4MP Fixed Starlight IR Bullet Camera 2560x1440@25fps, Metal+Plastic 1/2.7", 0.002Lux, Digital WDR, 50m IR, FOV: 103.4°, S+265/H.265/H.264, IP67 Mic-in, No Power Cable, No Reset Bottom, 512GB SD-Card 	IRR 43,585,000
	TC-C34GS Spec:15/E/Y/C/SD/2.8mm/V4.0		<ul style="list-style-type: none"> 4MP Fixed Starlight IR Bullet Camera Metal+Plastic Housing Upto 2688x1520@25fps, S+265/H.265/H.264 Built-In Mic, POE, DC12V, Smart IR, IR Range: 50m Support tripwire and perimeter, Support SD Card upto 512GB Min. illumination Color: 0.02Lux@F2.0 Operating Conditions: -30°-60°, 0-95% RH, IP67 	IRR 45,500,000
19	TC-C34HS Spec 13/E/Y/C/2.8mm/V4.0		2560x1440@25fps, Metal+Plastic 1/2.7", 0.002Lux, WDR 120dB, 30m IR FOV: 103.4°, S+265/H.265/H.264, IP66 Mic-in, No Reset Button, No SD-Card	IRR 41,690,000
22	TC-C34HS Spec 13/E/Y/C/SD/2.8mm/V4.0		<ul style="list-style-type: none"> 4MP Fixed Starlight IR Turret Camera 2560x1440@25fps, Metal+Plastic, 1/2.7", 0.002Lux, Digital WDR, 30m IR FOV: 99.7°, S+265/H.265/H.264, IP66 Mic-in, No Power Cable, No Reset Button 512GB SD-Card 	IRR 43,230,000
lite series				
24	TC-C35XS 13/E/Y/2.8MM/V4.0		<ul style="list-style-type: none"> KEY FEATURES -Default: Metal+Plastic, M, Metal Housing -Up to 2592x1944@20fps -S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6 -120dB WDR -Smart IR, IR Range: 30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -40°C-60°C, 0-95% RH -POE, IP67 	IRR 59,500,000
25	TC-C34KS Spec:13/E/Y/2.8mm/V4.0		<ul style="list-style-type: none"> Metal+Plastic Housing -Up to 2560x1440@25fps -S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6 -120dB WDR -Smart IR, IR Range: 30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -40°C-60°C, 0-95% RH -POE, IP67, IK10 	IRR 72,450,000
26	TC-C35KS Spec:13/E/Y/C/H/2.8mm/V4.0		<ul style="list-style-type: none"> - Full Metal Housing - Up to 2592x1944@30fps, 1920x1080@60fps - S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.002Lux@F1.6 Smart IR, IR Range: 30m - Support Video Analytics - Support Human/Vehicle Classification - Support Face Capture Mode - Built-in Mic, audio I/O 1/1, alarm I/O 1/1 - Plugin Free - Operating Conditions -40°C-65°C, 0-95% RH POE, IP67, IK10 	IRR 72,500,000

27	TC-C35WS I5/E/Y/C/H/2.8/V4.0		<ul style="list-style-type: none"> -Up to 2592x1944@30fps, 1920x1080@60fps -S+265/H.265/H.264/H.264H-JPEG -Min. illumination Color: 0.002Lux@F1.6 -Smart IR, IR Range: 50m -Support Video Analytics -Support Human/Vehicle Classification -Support Face Capture Mode -Built-in Mic, audio I/O 1/1, alarm I/O 1/1 -Plug-in Free 	IRR 67,000,000
	TC-C35WS Spec:I5/E/Y/M/4mm/V4.0		<ul style="list-style-type: none"> .5MPPixedStarlightIRBulletCamera .Metalhousing .Up toMax Resolution .IRRange50m.Built-inMic,IP67 SupportSDCardupto512GB .POE802.3af.MAX7W SupportSmartsurveillance S+265/H.265/H.264/H.264M/H.264H .OperatingConditions-40°-65°, 0-95% RH .Color:0.002Lux@(F1.6,AGCON),B/W:0LuxwithIR 	IRR 72,500,000
30	TC-C38KS SPEC: I3/E/Y/2.8mm/V4.0		<ul style="list-style-type: none"> 8MP Fixed Starlight IR Dome Camera -Metal+Plastic Housing -Up to 3840x2160@20fps -S+265/H.265/H.264 - Min. illumination Color: 0.003Lux@F1.6 -120dB WDR Smart IR, IR Range: 30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -35°-65°, 0-95% RH -POE, IP67, IK10 	IRR 97,000,000
31	TC-C38WS SPEC: I5/E/Y/M/2.8mm/V4.0		<ul style="list-style-type: none"> 8MP Fixed Starlight IR Bullet Camera Full Metal Housing -Up to 3840x2160@20fps -S+265/H.265/H.264 -Min. illumination Color: 0.003Lux@F1.6 -120dB WDR Smart IR, IR Range: 50m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -40°C-65°C, 0-95% RH -POE, IP67 	IRR 108,000,000
32	TC-C38WS SPEC: I5/E/Y/M/4mm/V4.0		<ul style="list-style-type: none"> 8MP Fixed Starlight IR Bullet Camera Full Metal Housing -Up to 3840x2160@20fps -S+265/H.265/H.264 -Min. illumination Color: 0.003Lux@F1.6 -120dB WDR Smart IR, IR Range: 50m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -40°C-65°C, 0-95% RH -POE, IP67 	IRR 108,000,000
33	TC-C38XS Spec: I3/E/Y/M/2.8mm/V4.0		<ul style="list-style-type: none"> 8MP Fixed Starlight IR Turret Camera -Full Metal Housing-Up to 3840x2160@20fps -S+265/H.265/H.264 -Min. illumination Color: 0.003Lux@F1.6 -120dB WDR Smart IR, IR Range: 30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -40°C-65°C, 0-95% RH -POE, IP67 	IRR 98,500,000
34	TC-R3105 I/B/L/EU		<ul style="list-style-type: none"> Video Input 5-ch Max Resolution 6MP Two-way Audio Input N/A Bandwidth Income 50Mbps; Outgoing 40Mbps 	IRR 37,950,000
35	TC-R3105 SPEC:I/B/P/L		<ul style="list-style-type: none"> S+265/H.265/H.264 video formats • 1xHDMI and 1xVGA simultaneous outputs • HDMI Video output at up to 4K resolution • Connectable to the third-party network cameras • 1 SATA interface, up to 8TB for 1 HDD • S+265 compression effectively reduces the storage space and costs by up to 75% • 1xRJ45 self-adaptive 10/100 Mbps networkinterface 	IRR 57,750,000
36	TC-R3108 SPEC: I/B		<ul style="list-style-type: none"> S+265/H.265/H.264 video formats • Up to 8-channel input 8 PoE ports • Supports live view, storage, and playback of the connected camera at up to 6MP resolution • HDMI Video output at up to 4K resolution • 1 SATA interfaces, up to 8TB for each HDD • S+265 compression effectively reduces the storage space and costs by up to 75% • 1xRJ45 self-adaptive 10/100 Mbps network interface • PoE Port: 8xRJ45 self-adaptive 10/100 Mbps network 	IRR 42,525,000
37	TC-R3110 SPEC : I/B/L/EU		<ul style="list-style-type: none"> 10-ch, 50Mbps/40Mbps, recording resolution up to 6MP, decoding ability 1*6MP, 3*1080p, 4*720p, video output: 1 HDMI & 1VGA simultaneous output, USB interface: 2xUSB 2.0 	IRR 42,550,000
37	TC-R3110 SPEC : I/B/V.03		<ul style="list-style-type: none"> • S+265/H.265/H.264 video formats • HDMI and VGA simultaneous output • HDMI Video output at up to 4K (3840 x 2160) resolution • 1 SATA interface, up to 10TB for 1 HDD • S+265 compression effectively reduces the storage space and costs by up to 75% 	IRR 47,850,000
40	TC-R3120 Spec: I/B/K/V3.0		<ul style="list-style-type: none"> 20-ch, 80Mbps/80Mbps, recording resolution up to 8MP, decoding ability 1*8MP, 4*1080p, 8*720p, video output: 1 HDMI & 1VGA simultaneous output, USB interface: 2xUSB 2.0, N+M 	IRR 98,785,000
41	TC-R3220 Spec:I/B/K		<ul style="list-style-type: none"> 20-ch, 120Mbps/100Mbps, recording resolution up to 8MP, decoding ability 1*8MP, 4*1080p, 8*720p, video output: 1 HDMI & 1VGA simultaneous output, alarm I/O 4/1, USB interface: 2xUSB 2.0, ANR, N+M 	IRR 130,900,000

42	TC-R3232 I/B/K/V3.1		<p>Video Input 32-ch Max Resolution 8MP Two-way Audio Input 1-ch, 3.5mm Bandwidth Income 160Mbps; Outgoing 48Mbps Output HDMI 1-ch, 3840x2160, 1920x1080, 1280x720, 1024x768, 1366x768, 1440x900, 1280x800 VGA 1-ch, 1920x1080, 1280x720, 1024x768, 1366x768, 1440x900, 1280x800 Screen Split 1/3/4/5/6/7/8/9/10/12/13/16/20A/20B/25/32 Audio Output 1xRCA</p>	IRR 159,850,000
43	TC-R3432 I/B/K/V3.1		<p>Video Input 32-ch Max Resolution 8MP Two-way Audio Input 1-ch, 3.5mm Bandwidth Income 160Mbps; Outgoing 48Mbps Output HDMI 1-ch, 3840x2160, 1920x1080, 1280x720, 1024x768, 1366x768, 1440x900, 1280x800 VGA 1-ch, 1920x1080, 1280x720, 1024x768, 1366x768, 1440x900, 1280x800 Screen Split 1/3/4/5/6/7/8/9/10/12/13/16/20A/20B/25/32 Audio Output 1xRCA</p>	IRR 209,300,000
44	TC-R3440 I/B/N/H/C		<p>HD Input-S*265/H.265/H.264 video formats - Connectable to the third-party network cameras - Up to 40-channel input - Supports live view, storage, and playback of the connected camera at up to 12MP resolution HD Output - HDMI and VGA simultaneous output - HDMI Video output at up to 4K (3840x2160) resolution HD Storage - 4 SATA interfaces, up to 10TB for each HDD - S*265 compression effectively reduces the storage space and costs by up to 75% HD Transmission - 2xRJ45 self-adaptive 10/100/1000 Mbps network interfaces, Various Applications - Centralized management of IP cameras, including configuration, information import/export, real-time information display, upgrades, etc. - Connectable to smart IP cameras from Tiandy and the recording, playing back, and backing up of VCA</p>	IRR 281,750,000
color maker series				
45	TC-C32XP I3W/E/Y/2.8MM/V4.2		<p>-Default: Metal+Plastic, M: Metal Housing -Up to 1920x1080@30fps -S*265/H.265/H.264 -Min. illumination Color: 0.0008Lux@F1.6 -Smart IR, IR Range: 30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -40°C-65°C, 0-95% RH -POE, IP67</p>	IRR 41,796,000
46	TC-C32XP W/E/Y/2.8MM/V4.2		<p>-Default: Metal+Plastic -Up to 1920x1080@30fps -S*265/H.265/H.264 -Min. illumination Color: 0.0008Lux@F1.6 -2 Warm lights, 15-20m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -POE, IP66</p>	IRR 39,600,000
49	TC-C34XP W/E/Y/M/2.8MM/V4.0		<p>1/2.8" CMOS, F1.6, Fixed Iris, Digital WDR, 0.0008Lux, 1920x1080@30fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE Metal model: cost added 4USD</p>	IRR 60,375,000
50	TC-C34UP W/E/Y/M/4MM/V4.0		<p>-Full Metal Housing -Up to 2560x1440@25fps -S*265/H.265/H.264 -Min. illumination Color: 0.0002Lux@F1.0 -120dB WDR -4 Warmlights, 20-30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -40°C-60°C, 0-95% RH -POE, IP67</p>	IRR 97,405,000
51	TC-C32WP I5/E/Y/2.8MM/V4.0		<p>-Up to 1920x1080@30fps -S*265/H.265/H.264 -Min. illumination Color: 0.0008Lux@F1.6 -2 Warm lights, 15-20m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -POE, IP67</p>	IRR 43,870,000
52	TC-C32WP Spec:I5W/E/Y/2.8mm/V4.2		<p>-Up to 1920x1080@30fps -S*265/H.265/H.264 -Min. illumination Color: 0.0008Lux@F1.6 -2 Warm lights, 15-20m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -POE, IP67</p>	IRR 52,416,000
eco pro				
	TC-C32MS SPEC:I3/A/E/Y/M/C/H/2.7-13.5MM/V4.0		<p>-Full Metal Housing -Motorized Lens 2.7-13.5mm -Up to 1920x1080@30fps -S*265/H.265/H.264-M-JPEG -Min. illumination Color: 0.001Lux@F1.6 -Smart IR, IR Range: 50m -Support Video Analytics</p>	IRR 79,000,000
	TC-C32KS Spec: I3/E/Y/C/H/2.8mm/V4.0		<p>-Full Metal Housing -Up to 1920x1080@30fps -S*265/H.265/H.264-M-JPEG -Min. illumination Color: 0.001Lux@F1.6 -Smart IR, IR Range: 30m -Support Video Analytics</p>	IRR 58,937,500
	TC-C32KS Spec: I3/E/Y/C/H/2.8mm		<p>-Full Metal Housing -Up to 1920x1080@30fps -S*265/H.265/H.264-M-JPEG -Min. illumination Color: 0.001Lux@F1.6 -Smart IR, IR Range: 30m -Support Video Analytics</p>	IRR 58,937,500

	TC-C35KS Spec:13/E/Y/2.8mm/V4.0		<ul style="list-style-type: none"> 5MPFixedStarlightIRDomeCamera -Metal+PlasticHousing -UptoMax.Resolution -IRRange:30m -Built-inMic,IP67,DC12V,POE -SupportSmartSurveillance -SupportSDCardupto64GB -S+265/H.265/H.264/H.264M/H.264H -OperatingConditions-40°C-65°C,0-95%RH -Color:0.002Lux@(F1.6,AGCON),B/W:0LuxwithIR 	IRR 71,585,000
	TC-C32WS Spec:15/E/Y/C/H/4mm/V4.		<ul style="list-style-type: none"> 2MPFixedStarlightIRBulletCamera -Metal+PlasticHousing -Upto1920x1080@30fps -SmartIR,IRRange:50m -S+265/H.265/H.264,POE,IP67 -Supporttripwireandperimeter -AudioIO1/1,AlarmIO1/1 -Built-inMic,SDCardSlot,ResetButton -OperatingConditions-35°-65°,0-95%RH -Min.illuminationColor:0.002Lux@F1.6 	IRR 51,250,000
	TC-C34LP Spec:15/A/E/M/H/2.7-13.5mm		<ul style="list-style-type: none"> -Full Metal Housing -Motorized Lens 2.7-13.5mm -Up to 2560x1440@30fps, 1920x1080@60fps -S+265/H.265/H.264M-JPEG -Min. illumination Color: 0.0004Lux@F1.2 -Support Video Analytics -Support Human/Vehicle Classification 	IRR 156,200,000
54	TC-C35MS 13/A/E/Y/M/2.8-12MM		<ul style="list-style-type: none"> -Full Metal Housing -Motorized Lens 2.7-13.5mm -Up to 2592x1944@20fps -S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6 Smart IR, IR Range: 30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Audio IO 1/1, Alarm IO 1/1 -POE, IP67, IK10 	IRR 99,960,000
	TC-C35MS Spec:13/A/E/Y/M/C/H/2.7-13.5mm		<ul style="list-style-type: none"> 5MPMotorizedStarlightIRDomeCamera -FullMetalHousing -MotorizedLens2.8-12mm -Upto2592x1944@20fps -S+265/H.265/H.264 -POE,IP67,IK10 	IRR 99,960,000
	TC-C35MS Spec:13/A/E/Y/M/C/H/2.7-13.5mm/V4.0		<ul style="list-style-type: none"> TC-C35MS Spec:13/A/E/Y/M/C/H/2.7-13.5mm/V4.0 64 IRR99,960,000 5MP 5MPMotorizedStarlightIRDomeCamera -FullMetalHousing -MotorizedLens2.8-12mm -Upto2592x1944@20fps -S+265/H.265/H.264 -POE,IP67,IK10 	IRR 99,960,000
56	TC-C35US 18/A/E/Y/M/C/H/2.7-13.5MM/V4.0		<ul style="list-style-type: none"> -Full Metal Housing -Motorized Lens 2.7-13.5mm -Up to 2592x1944@30fps, 1920x1080@60fps -S+265/H.265/H.264M-JPEG -Min. illumination Color: 0.001Lux@F1.6 Smart IR, IR Range: 80m -Support Video Analytics Support Human/Vehicle Classification -Support Face Capture Mode -Built-in Mic, Audio IO 1/1, alarm IO 2/1 -POE, IP67 	IRR 99,960,000
57	TC-C35TS Spec: 18/A/E/Y/M/H/2.7-13.5mm		<ul style="list-style-type: none"> -Full Metal Housing -Motorized Lens 2.7-13.5mm -Up to 2592x1944@30fps, 1920x1080@60fps -S+265/H.265/H.264M-JPEG -Min. illumination Color: 0.001Lux@F1.6 -Smart IR, IR Range: 80m -Support Video Analytics 	IRR 149,100,000
PRO-LPR series				
58	TC-C34WS 15W/E/Y/2.8MM/V4.2		<ul style="list-style-type: none"> 1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 50m IR, 0.002Lux, 2560x1440@25fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE Metal model: cost added 4USD 	IRR 56,350,000
59	TC-C34WS 15W/E/Y/M/2.8MM/V4.2		<ul style="list-style-type: none"> 1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 50m IR, 0.002Lux, 2560x1440@25fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE Metal model: cost added 4USD 	IRR 59,290,000
60	TC-C34XS 13W/E/Y/2.8MM/V4.2		<ul style="list-style-type: none"> Default: Metal+Plastic -Up to 2560x1440@25fps -S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6-120dB WDR Smart IR, IR Range: 30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -POE, IP67 	IRR 53,900,000
NVR-PRO				
62	TC-R3440 Spec:1/B/N		<ul style="list-style-type: none"> 4K/265/H.265/H.264 video formats -Connectable to the third-party network cameras -Up to 40 IP cameras can be connected -Supports live view, storage, and playback of the connected camera at up to 12MP resolution -HDMI and VGA independent outputs -HDMI Video output at up to 4K (3840 x 2160) resolution HD Storage -4 SATA interfaces connectable for recording and backup, up to 10TB for each HDD 	IRR 446,775,000

	TC-R3220 Spec:I/B/P16/K/V3.0		<ul style="list-style-type: none"> HD Input: Plug and play S+265/H.264/H.264 video formats Connectable to the third-party network cameras Up to 20-channel input + 16 PoE ports Supports live view, storage, and playback of the connected camera at up to 8MP resolution HD Output <ul style="list-style-type: none"> 1xHDMI and 1xVGA simultaneous outputs HDMI Video output at up to 4K (3840 x 2160) resolution HD Storage + 2 SATA interfaces, up to 10TB for each HDD S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission <ul style="list-style-type: none"> 1xRJ45 self-adaptive 10/100/1000 Mbps network interface 	IRR 229,400,000
63	TC-R3840 Spec:I/B/N		<ul style="list-style-type: none"> Upto40IPcamerascanbeconnected S+265/H.265/H.264videoformats Upto12MPResolution HDMIandVGA HDMIvideooutputupto4K(3840x2160)resolution SATAinterfaces,upto10TBforeachHDD 2xRJ45self-adaptive10/100/1000Mbpsnetworkinterfaces 2xRJ45self-adaptive10/100/1000Mbpsnetworkinterfaces 	IRR 498,250,000
SPEED DOM -SMD				
64	TC-H324S 23X/I/E/C/V3.0		PoE+, 1/2.8" Starlight sensor, 1080P @30fps, 150m IR, 25x optical zoom, Speed 0.1"-200"/s, Heater, TVS 6000V protection; Low Illumination: 0.002Lux	IRR 200,100,000
66	TC-H324S 25X/I/E		<ul style="list-style-type: none"> Up to 1920X1080@30fps Min. illumination Color: 0.001Lux@F1.5 Optical zoom: 25x, digital zoom 16x Support Human/Vehicle Classification Smart IR, IR Range: 150m S+265/H.265/H.264/M-JPEG Plugin Free IP66 	IRR 321,195,000
	TC-H326S Spec:33X/I/E++/A		<ul style="list-style-type: none"> 2MP33xStarlightIRPOEAIPTZCamera Upto1920x1080@60fps SmartIR,IRRange:200m,S+265/H.265/H.264/M-JPEG IP66,PluginFree,SupportAuto-tracking Opticalzoom:33x,digitalzoom 16x SupportHuman/VehicleClassification Min.illuminationColor:0.001Lux@F1.5 Intelligentmonitoring/FaceCapturemode 	IRR 693,600,000
	TC-H356S Spec:30X/I/E++/A/V3.0		<ul style="list-style-type: none"> 5MP30xStarlightIRPOEAIPTZCamera SupportAuto-tracking Upto2880x1620@30fps,SmartIR,IRRange:200m S+265/H.265/H.264/M-JPEG,PluginFree,IP66 Min.illuminationColor:0.001Lux@F1.5 Opticalzoom:30x,digitalzoom 16x Intelligentmonitoring/FaceCapturemode SupportHuman/VehicleClassification 	IRR 748,000,000
67	TC-H354S 23X/I/E/V3.0		<ul style="list-style-type: none"> 5MP 23x Starlight IR PoE AI PTZ Camera-Upto 2880x1620@30fps Optical zoom: 23x, digital zoom 16x Smart IR, IR Range: 150m S+265/H.265/H.264/M-JPEG Intelligent monitoring Support Human/Vehicle Classification-Plugin Free-IP66 	IRR 351,750,000